

4

3

2

1

ZONE	REV	DESCRIPTION	ECN	DATE	APVD
	1	INITIAL RELEASE		9/15/14	
B3	2	REMOVE VOLTAGE RATING		9/30/14	
A4	3	CHANGE SUPPLIER INFO		10/22/14	

CONN TYCO: 353908-6
 TERM TYCO: 353907-1



ITEM	DESCRIPTION	AWG	MAX OD (MM)	COLOR	QTY (PCS)	LENGTH (MM)
1	STRANDED WIRE	24	1.12	RED	1	600
2	STRANDED WIRE	24	1.12	BLACK	1	600
3	STRANDED WIRE	24	1.12	VIOLET	1	600
4	STRANDED WIRE	24	1.12	GREY	1	600
5	CONN TYCO: 353908-6			WHITE	1	
6	TERM TYCO: 353907-1				4	

NOTES FOR WIRES:

- MUST MEET UL VW-1
- TEMPERATURE RATED AT -40° C TO 105° C MINIMUM
- MUST BE EITHER ONE OF THE FOLLOWING TYPE: UL10362, UL1213 OR UL11028
- WIRE INSULATION COLOR MUST BE OPAQUE. CLEAR OR TRANSLUCENT WIRE INSULATION IS NOT ALLOWED

SUPPLIER CONTACT INFO: AVNET.COM

<p align="center">-CONFIDENTIAL-</p> <p>THIS DOCUMENT IS AND CONTAINS CONFIDENTIAL AND TRADE SECRET INFORMATION OF XICATO INC.</p> <p>THIS DOCUMENT IS LOANED FOR LIMITED PURPOSES ONLY AND REMAINS THE PROPERTY OF XICATO INC. IT IS TO BE RETURNED UPON REQUEST AND IN ALL EVENTS UPON COMPLETION OF PURPOSE OF THE LOAN.</p> <p>NEITHER IT NOR THE INFORMATION IT CONTAINS MAY BE REPRODUCED, USED, OR DISCLOSED TO PERSONS NOT HAVING A NEED TO KNOW CONSISTENT WITH THE PURPOSE OF THE LOAN WITHOUT WRITTEN CONSENT OF XICATO INC.</p>	<p>UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS. STANDARD TOLERANCES ARE:</p> <p>0-10± 0.1 10-50± 0.15 50-100± 0.20 100+± 0.25 ANGLES ±1.5°</p>	<p>DATE: 9/30/14</p> <p>DSR: WK</p> <p>REL.:</p> <p>PROD.:</p> <p>ENGR.:</p> <p>CHKD.:</p> <p>CHKD.:</p>	<p align="center">XICATO INC</p> <p>TITLE TYCO 2829114-2 WIRE HARNESS 600MM</p> <p>DWG SIZE C</p> <p>PART NUMBER X02219</p> <p>SCALE: 5.000</p>	<p>REV. 3</p> <p>SHEET 1 OF 1</p>
--	--	--	---	-----------------------------------

4

3

2

1